

ABC (DRY POWDER) STORE PRESSURE TYPE FIRE EXTINGUISHERS

IDEAL USE:

Homes, Office, Buildings, Warehouses, Farms, Wood, Working area etc.



PERFORMANCE DATA

CAPACITY IN KG	1 KG	2 KG	4 KG	6 KG	9 KG
I.S. SPECIFICATION NO.	IS 15683:2018	IS 15683:2018	IS 15683:2018	IS 15683:2018	IS 15683:2018
FIRE RATING	1A,21B	1A,21B	2A,55B	3A,89 B	4A,144 B
OVERALL HEIGHT (MM)	320 MM	375 MM	460 MM	480 MM	585 MM
COMPLETE WEIGHT(APPR.KG)	02 kg	3.3 kg	6.2 kg	8.6 kg	12.5 kg
EMPTY WEIGHT(APPR.KG)	01 kg	1.3 kg	2.2 kg	2.6 kg	3.5 kg
OPERATING TEMP. °C	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C
DIA.OF CYLINDER(M M)	86± 10mm	108± 10mm	140±10mm	160±10mm	175±10mm
RANGE OF DISCHARGE(M)	2 m	2 m	2 m	2 m	2 m
DURATION OF DISCHARGE(SEC)	8 Sec	8 Sec	13 Sec	13 Sec	15 Sec
TEST PRESSURE(MIN)	35 kgf/cm ²	35 kgf/cm ²	35 kgf/cm ²	35 kgf/cm ²	35 kgf/cm ²
WORKING PRESSURE	15 kgf/cm ²	15 kgf/cm ²	15 kgf/cm ²	15 kgf/cm ²	15 kgf/cm ²
BRUST PRESSURE(MIN)	55 kgf/cm ²	55 kgf/cm ²	55 kgf/cm ²	55 kgf/cm ²	55 kgf/cm ²
APPROVALS	BIS	BIS	BIS	BIS	BIS



A Solid Combustible
Materials such as
Paper, Wood, Textiles



B Flammable Liquids
such as Petrol,
Diesel, Oil



C Flammable Gases
such as Natural Gas,
Propane



Electrical Fires such
as Short Circuiting
Equipment